

OSG BASICS

HMD & HMF available CRS & A40. Doors have flush top, inverted bottom, closer reinforce, non-handed, universal standard to heavy weight hinge prep. All hmf are brake formed. Below is what we keep in stock. Other options available as non stock. **Doors are in stock with Amweld locations (standard), Ceco, Curries, Republic, Pioneer, & Mesker locations...all in stock at no extra up charge.**

- **M series masonry hmf** – standard welded type hmf. 16 gauge. Available 2'0" – 8'0" wide in 68, 70, 80 height. Up to 3 hour fire rating. Base anchors welded in.
 - In stock:
 - **5 ¾ CRS** - 26/28/30/36/40/60 & 30 4" face heads with 68, 70, 80 jambs. Blank jambs in 70. Blank stick in 8'0" & 10'0" lengths. Strike & Blank Mullions in 7'0" & 8'0".
 - **5 ¾ A-40** - 30/36/40/60 & 30/40/60 4" face heads with 68, 70, 80 jambs. Blank jambs in 70 & 80. Blank stick in 8'0" & 10'0" lengths. Strike & Blank Mullions in 7'0" & 8'0".
 - 7 ¾ - 30 heads with 68 & 70 jambs CRS & A40.
 - 8 ¼ - 30 & 60 heads with 70 jambs only. CRS only.
 - Curries, Pioneer, Mesker, & Republic locations in 68 & 70 A-40 5 ¾. (Curries & Pioneer in 70 jambs only).
- **D series drywall hmf** – standard knockdown drywall hmf. 16 gauge. Available 2'6" – 6'0" wide in 68 & 70 height. Up to 1-1/2 hour fire rating.
 - In stock:
 - 4 ½" – 3068 & 3070 CRS.
 - 5 5/8" – 28/30/60 heads 68 & 70 jambs CRS.
 - 5 7/8" – 26/28/30/36/40/60 heads with 68, 70 jambs CRS.
 - 7 ¼", 7 ¾", & 8 ¼" – 30/60 heads 68 & 70 jambs CRS.
 - 8 ¾" - 30/60 heads 70 jambs CRS.
 - Curries, Ceco, Pioneer, Mesker, & Republic locations in 68 & 70 CRS in 5 7/8.
- **Infinity P series hmd** – polystyrene core. Available in 16, 18, & 20 gauge CRS or Galv. Seamless welded edge tack welded on 2" centers. 161, 86, or rim panic reinforce.
 - In stock:
 - 2068 thru 4080 18 gauge A-40
 - 3068 & 3070 18 gauge CRS
 - 3068 & 3070 20 gauge A-40 & CRS
 - 3068 & 3070 16 gauge A-40
 - 3070 18 gauge A-40 steel stiffened (22ga stiffeners) in 161 or 86
- **Infinity H series hmd** – honeycomb core. Available in 16, 18, & 20 gauge CRS or Galv. Seamless welded edge tack welded on 2" centers. 161, 86, or rim panic reinforce.
 - In stock:
 - 2068 thru 4070 18 gauge CRS
 - 3068 & 3070 18 gauge A-40
 - 3068 & 3070 20 gauge CRS
 - 3068 & 3070 20 gauge A-40
- **Infinity 6 panel embossed hmd** - polystyrene core. Available in 16, 18, & 20 gauge CRS or Galv. Seamless welded edge tack welded on 2" centers. 161, 86, or rim panic reinforce.
 - In stock:
 - 3068 & 3070 18 ga CRS & A-40
- **Eagle hmd** – honeycomb & polystyrene core. Available in 18 & 20 gauge CRS or Galv. Flush or 6 panel. Edge seam construction. 161 or 86. 3068 & 3070. Amweld locations standard. Also keep in stock in Ceco, Curries, & Mesker locations.
- **Astragals** – 70 & 80 in ASA, ASA/FB.

OSG Nomenclature:

6G = 16 gauge galv 8G = 18 gauge galv 2G = 20 gauge galv
6C = 16 gauge crs 8C = 18 gauge crs 2C = 20 gauge crs
C = standard 161 lock prep
L = 161 prep with thru-bolt holes (squashed turtle prep)